

Eurovent ALUFIX

Single-sided tape made of polyethylene foil, aluminum coating and acrylic dispersion adhesive. Designed for sealing and repairing aluminum foils, aluminum-based or aluminum-coated construction materials.



Advantages:

- high adhesive strength
- solvent-free
- UV resistance

Technical data:

Parameter	Value
Material	PE foil, acrylic dispersion glue
Dimensions	50 mm x 25 mm*; 50 mm x 50 mm; 75 mm x 50 mm*
Thickness	0,051 mm
Maximum tensile strength	100 N/25 mm
Elongation at break	140%
Temperature resistance	-30 to +90°C
Application temperature	Recommended from +5°C up to +40°C
UV resistance	Excellent
Packaging	50 mm x 25 mm: 44 rolls in a box, 42 boxes on a pallet 50 mm x 50 mm: 36 rolls in a box, 36 boxes on a pallet 75 mm x 50 mm: 36 rolls in a box, 24 boxes on a pallet
Storage	Room temperature, enclosed spaces, in original packaging

* Against order

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016

Eurovent **ALUFIX**

Application:

Tape is designed for sealing and repairing vapour-insulation and vapour-permeable foils based on aluminum as well as metalized plastics. Recommended also for repairing all kinds of damages such as holes, cuts and installation punctures.

Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016