

Eurovent TOPBAND

Single-sided tape made of polypropylene nonwoven and acrylic dispersion adhesive. Designed for sealing and repairing roof membranes and other polypropylene-based construction materials. Tape protects against the penetration of moisture and wind while retaining the vapour-permeability of the membrane with its breathing surface.



Advantages:

- high adhesive strength
- tear resistance
- vapour-permeability

Technical data:

Parameter	Value
Material	Non-woven PP, acrylic dispersion adhesive.
Color	Grey
Width	50 mm
Length	25 m
Thickness	0,18 mm glue + non-woven 0,5 mm
Grammage of adhesive	230 g/m ²
Storage	In room temperature, in enclosed spaces.

Parameter	Value
Peel adhesion	26 N/25 mm
Processing temperature	from -10°C
Temperature of application	recommended from +5°C up to 40°C
Temperature resistance	-40°C up to +100°C
UV resistance	Up to 4 months
Package	12 rolls, 60 rolls on a pallet.

Application:

Tape is designed for sealing and repairing roof membranes, housewraps and other polypropylene-based construction materials. Recommended for repairing all kinds of damages such as holes, cuts and installation punctures. Binds with surfaces such as wood, brick and smooth concrete.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 11/2015

Eurovent **TOPBAND**

Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 11/2015